




BEARING DRIVESHAFT, INC.



3.937 Inch | 100 Millimeter x 5.906 Inch | 150 Millimeter x 0.945 Inch | 24 Millimeter SKF NU 1020 M/C3 Cylindrical Roller Bearings

Bearing No. NU 1020 M/C3

NU 1020 M/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	3.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.549
EAN	7316577012944
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	100MM Bore; Straight Bore Profile; 150MM Outside Diameter; 24MM Width;



BEARING DRIVESHAFT, INC.

	Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Inte
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 1020 M/C3
Weight / LBS	3.411
B	0.945 Inch 24 Millimeter
d	3.937 Inch 100 Millimeter
D	5.906 Inch 150 Millimeter
bore diameter:	100 mm
static load capacity:	114 kN
outside diameter:	150 mm
precision rating:	RBEC 1 (ISO Class Normal)
overall width:	24 mm
maximum rpm:	7500 RPM
flanges:	(2) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	24 mm



BEARING DRIVESHAFT, INC.

operating temperature range:	Maximum of +300 ° F
fillet radius:	1.5 mm
dynamic load capacity:	85.8 kN
series:	NU10